



## RHOBALAVIA L302

(RHOBACLEAN 330 WL-V)

ARTICLE- NO. 030105

Concentrated hydro cleaner for paint application equipment and water-based paints.

### APPLICATION

High yielding concentrate, which is always used diluted with water.

**CIP cleaning of lines carrying paint:** The cleaning solution is pumped in the circuit to dissolve all lacquer residues. If the desired cleaning effect is not achieved, a further rinse must be carried out (with increased concentration if necessary). Then rinse the pipe system with water.

**Manual cleaning:** The cleaning solution is applied using a suitable cleaning pad. Then rinse with water. Due to the large number of lacquer and paint systems and materials, preliminary tests are recommended.

Application	Concentration	Contact time
CIP-Cleaning	5-15 Vol.%	up to 15 min.
Manual cleaning	up to 50 Vol.%	depending on the type of soiling

### PRODUCT FEATURES

- concentrated and easy to dose
- for cleaning water-based paints
- for cleaning paint lines, atomiser bells, spray guns, etc.
- does not attack material surfaces such as steel, aluminium and non-ferrous metals
- low-foaming application

### CONCENTRATION DETERMINATION

A concentration determination is possible by means of a hand refractometer (faktor = 2.00)  
concentration (Vol.%) = [value read] x 2.00

### TECHNICAL DATA

Appearance	Colorless liquid
Density at 20 °C	approx. 0.95 g/ml
Flash point	> 60°C
pH-value at 20 °C	approx. 10

Before application, test material compatibility at an inconspicuous area. Follow the cleaning and care instructions provided by the manufacturer. We cannot be held liable for improper use and resulting damages.

### STORAGE

Storage temperature: 5-30 °C

Shelf life: 12 months