



RHOBA PURIA F104

(RHOBAFLOCK F 122 SU)

ARTICLE-NO. 020123

Special flocculating agent

APPLICATION

RHOBA PURIA F104 reliably flocculates pigmented paints, 1 or 2-component paints, polyester paints and nitrocellulose lacquers. In combination with **RHOBA PURIA K202** it also flocculates water-based paints. The product can be used in all water booths, water-sprinkled spraying systems and paint spraying machines. The paint particles coagulate and are flocculated. **RHOBA PURIA F104** also debonds the paint particles so that they can be easily removed.

The application quantity for flocculation treatment depends on the nature of the circulating water to be treated, the available system technology and the intended use.

It is precisely determined by our laboratory and our application engineers "on site" and is used in accordance with our laboratory tests!

PROPERTIES

- suitable for solvent-based and water-based paints
- is liquid and easy to dose (manually or automatically)
- mixes quickly and homogeneously in the circulating water
- forms a stable, easily dischargeable flake
- is also excellently suited for the use of standard paint coagulate discharge devices, e.g. slides, separators, decanters, centrifuges, etc.
- is also used in industrial water treatment
- is non-abrasive, protects pumps and pipelines

TECHNICAL SPECIFICATIONS

Appearance	white liquid
Density at 20 °C	approx. 1,03 g/ml
pH-value at 20 °C	3-4

Before use, check material compatibility on an inconspicuous area. Observe the manufacturers cleaning and care instructions! No liability can be accepted for improper use and resulting damage.

STORAGE

Storage temperature: 5-30 °C

Shelf life: 12 months