TECHNICAL INFORMATION – PAINT STRIPPING

RHOBA SUPRA E501

ARTICLE-NO. 100003

Solvent-based paint stripper

APPLICATION

RHOBA SUPRA E501 is a ready-to-use paint remover that reliably removes a variety of cured polyurethanes, 1 K and 2 K paints, epoxy paints, dried paints, as well as oils, greases and environmental dirt by spraying, rinsing, pumping, dipping, brushing and wiping.
RHOBA SUPRA E501 is used undiluted and at room temperature, heating up to 40° C is possible and can shorten the paint stripping time.

The parts to be stripped should be cleaned of coarse dirt and oil and must be dry. Ingressed water reduces the paint stripping performance and considerably reduces the bath service life; in addition, corrosion can occur on light metals.
Depending on the type, layer thickness and age of the organic coating, the paint removal time ranges from a few minutes to several hours. A light bath movement supports the stripping process and experience has shown that it shortens the stripping time.
Once the paint stripping process is complete, the parts are rinsed in a water bath or sprayed with a strong jet of water, ensuring that no water gets into the paint stripper bath.

PRODUCT FEATURES

- has a very high dissolving capacity, even hardened PU systems can be dissolved in immersion baths, molds and tools can be cleaned
- can be easily washed off with water
- reliably cleans nozzles, mixers, spray heads, pipes, floors and objects soiled with paint
- due to the large number of different coating systems and substrates, we always recommend carrying out preliminary tests

TECHNICAL SPECIFICATIONS

Appearance	colourless, clear liquid
Density at 20 °C	approx. 1,03 g/ml
Flash point	91 °C

Before application, test material compatibility at an inconspicuous area. Follow the cleaning and care instructions provided by the manufacturer. We cannot be held liable for improper use and resulting damages.

STORAGE

Storage temperature: 5-30 °C
Shelf life: 12 months

Stand: 2025-06-13

RHOBA-Chemie GmbH
Gustav-Winkler-Str. 32 a | D - 33699 Bielefeld
Tel. +49 521 4 17 17 4 | Fax +49 521 4 17 17 60
E-Mail: info@rhoba-chemie.com | **www.rhoba-chemie.com**

RHOBA-Chemie®
SCHNELL. FLEXIBEL. CLEVER.